

# Cisco UCS B200 M3 Blade Server

Server - blade - 2-way - no CPU - RAM 0 GB - SAS - hot-swap 2.5" bay(s) - no HDD - MGA G200e - monitor: none - DISTI

Group	Barebones
Manufacturer	Cisco
Manufacturer item no.	UCSB-B200-M3-CH
EAN/UPC	0882658485350



## Description

Delivering performance, versatility, and density without compromise, the Cisco UCS B200 M3 Blade Server addresses the broadest set of workloads, from IT and web infrastructure to distributed database.

## Main features

Product Description	Cisco UCS B200 M3 Blade Server - blade - no CPU - 0 GB - no HDD
Type	Server - blade
Server Scalability	2-way
Processor	No CPU
Processor Socket	LGA2011 Socket
RAM	0 GB (installed) / 768 GB (max) - DDR3 SDRAM - ECC
Storage Controller	RAID (SATA 6Gb/s / SAS 6Gb/s) (LSISAS2004)
Server Storage Bays	Hot-swap 2.5"
Hard Drive	No HDD
Optical Storage	No optical drive
Graphics Controller	Matrox MGA G200e
Dimensions (WxDxH)	20.3 cm x 62 cm x 5 cm
Weight	4.36 kg
Pricing Type	DISTI

## Extended details

General	
Type	Server
Product Form Factor	Blade
Server Scalability	2-way
Hot-Swap Bays Qty	2
Processor / Chipset	
CPU	No CPU
Max CPU Qty	2
CPU Usability	Usable

CPU Socket	LGA2011 Socket
Chipset Type	Intel C600
	<b>RAM</b>
Installed Size	0 GB / 768 GB (max)
Technology	DDR3 SDRAM - ECC
Form Factor	DIMM 240-pin
Slots	24 (Total) / 24 (empty)
Features	Registered, Load-Reduced DIMM (LRDIMM)
RAM Supported	384 GB registered - ECC   768 GB Load-Reduced - ECC
	<b>Hard Drive</b>
Type	No HDD
	<b>Storage Controller</b>
Type	RAID - integrated
Controller Interface Type	SATA 6Gb/s / SAS 6Gb/s
Storage Controller Name	LSISAS2004
RAID Level	RAID 0, RAID 1
	<b>Optical Storage</b>
Type	No optical drive
	<b>Monitor</b>
Monitor Type	None.
	<b>Graphics Controller</b>
Type	Integrated
Graphics Processor	Matrox MGA G200e
	<b>Networking</b>
Remote Management Controller	Cisco Integrated Management Controller
	<b>Expansion / Connectivity</b>
Bays	2 (total) / 2 (free) x hot-swap 2.5"
Slots	2 (total) / 2 (free) x CPU   24 (total) / 24 (free) x DIMM 240-pin   2 (total) / 2 (free) x expansion slot
Interfaces	1 x KVM
	<b>Miscellaneous</b>
Compliant Standards	CISPR 22 Class A, BSMI CNS 13438 Class A, CISPR 24, EN 61000-3-2, VCCI Class A ITE, EN 61000-3-3, EN55024, EN55022 Class A, AS/NZS 60950-1, ICES-003 Class A, FCC CFR47 Part 15, UL 60950-1, IEC 60950-1, EN 60950-1, CSA C22.2 No. 60950-1, GB 4943, EN 300 386
Pricing Type	DISTI
	<b>Manufacturer Warranty</b>
Service & Support	Limited warranty - replacement - 3 years - on-site - response time: next business day
	<b>Dimensions &amp; Weight</b>
Width	20.3 cm

Depth	62 cm
Height	5 cm
Weight	4.36 kg

**Environmental Parameters**

Min Operating Temperature	10 °C
Max Operating Temperature	35 °C
Humidity Range Operating	5 - 93% (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.