

APC Smart-UPS SMT1500RM2UC - UPS (rack-mountable)

AC 120 V - 1 kW - 1440 VA - 1 x - USB - serial - output connectors: 6 - 2U - black - with APC SmartConnect - for P/N: AR4018SPX432 - AR4024SP - AR4024SPX429 - AR4024SPX431 - AR4024SPX432 - NBWL0356A



Group	Power Supply
Manufacturer	APC
Manufacturer item no.	SMT1500RM2UC
EAN/UPC	0731304322801

Description

APC SmartConnect makes Smart-UPS more adaptable and easier to deploy than ever before, enabling you to view the status of your UPS through a secure web portal. Through this intuitive remote management interface, you'll receive automatic notifications, firmware updates, and advanced support; providing you with added value - and more importantly - added peace of mind.

Main features

Product Description	APC Smart-UPS SMT1500RM2UC - UPS - 1 kW - 1440 VA - with APC SmartConnect
Device Type	UPS - rack-mountable
Rack Size	2U
Weight	26.5 kg
Input Voltage	AC 120 V
Output Voltage	AC 120 V ± 5%
Power Capacity	1 kW / 1440 VA
Input Connectors	1 x power NEMA 5-15P
Output connectors	6 x power NEMA 5-15R
Battery	Lead Acid
Batteries Qty	1 1
Run Time (Up To)	7.2 min at full load
Networking	USB, serial
Colour	Black
Dimensions (WxDxH)	43.2 cm x 47.7 cm x 8.6 cm
Environmental Standards	ENERGY STAR
Bundled with	APC SmartConnect
Designed For	P/N: AR2487G, AR3100W, AR3105SP, AR3105W, AR3140G, AR3140W, AR3150W, AR3155SP, AR3155W, AR3300W, AR3305W, AR3340G, AR3355SP, AR3355W, AR4018IX429, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4024IX431, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4038IX432, NBWL0356A

Extended details

General	
Device Type	UPS - rack-mountable
Height (Rack Units)	2U
Colour	Black
Bundled with	APC SmartConnect
Power Device	
UPS Technology	Line interactive
Input Voltage	AC 120 V
Input Voltage Range	AC 82 - 144 V
Input Voltage Range (Adjustable)	AC 75 - 154 V
Frequency Provided	50/60 Hz \pm 3Hz
Frequency Required	50/60 Hz \pm 3Hz
Input Connectors	1 x power NEMA 5-15P
Power Output Connectors Details	6 x power NEMA 5-15R
Output Voltage	AC 120 V \pm 5% - 50/60 Hz
Power Capacity	1 kW / 1440 VA
Output Waveform	Sinewave
Surge Suppression	Yes
Surge Energy Rating	680 Joules
Circuit Protection	Circuit breaker
Efficiency	98.3% at 100% Load, 97.2% at 25% Load, 98.2% at 50% Load, 98.3% at 75% Load
Battery	
Quantity	1 1
Technology	Lead Acid
Run Time (Up To)	7.2 min at full load 335 min at 50 Watts 190 min at 100 Watts 92 min at 200 Watts 55.9 min at 300 Watts 37 min at 400 Watts 18.8 min at 600 Watts 14 min at 700 Watts 10.8 min at 800 Watts 8.6 min at 900 Watts 25.9 min at 500 Watts
Recharge Time	3 hours
Transfer Time	6 ms
Features	Maintenance free, sealed, leak-proof
Networking	
Remote Management Interface	USB, serial
Expansion / Connectivity	
Interfaces	1 x management (USB) - 4 pin USB Type B
Expansion Slots	1 (total) / 1 (free) x SmartSlot
Miscellaneous	
Cables Included	Serial cable - external USB cable - external Power cable - integrated - 2.44 m
Rack Mounting Kit	Included

Equipment Protection Value	150000 US Dollars
Features	Audible alarm, LCD display, Automatic Voltage Regulation (AVR), LED indicators, cold-start function, automatic self-test, hot-swappable batteries, energy metre
Compliant Standards	CSA, ICES-003, UL 1449, UL 1778, CSA C22.2 No. 107.1, RoHS, REACH, FCC Part 15 Class B
Software / System Requirements	
Software Included	Drivers & Utilities
Environmental Standards	
ENERGY STAR	Yes
Manufacturer Warranty	
Service & Support	Limited warranty - replace or repair - 3 years Limited warranty - batteries - 2 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95%
Sound Emission	45 dBA
Dimensions & Weight	
Width	43.2 cm
Depth	47.7 cm
Height	8.6 cm
Weight	26.5 kg
Dimensions & Weight (Shipping)	
Shipping Width	59 cm
Shipping Depth	61 cm
Shipping Height	23.5 cm
Shipping Weight	32.12 kg
Compatibility Information	

Designed For

P/N: ACCS1000, ACCS1001, ACCS1002, ACCS1003, ACCS1004, ACCS1005, ACCS1006, ACCS1007, ACDC1015, ACDC1016, ACDC1017, ACDC1019, ACDC1020, ACDC1021, ACDC2513, ACF001, ACF002, ACF003, ACF101BLK, ACF102BLK, ACF201BLK, ACF400, ACF600, AP5017, AP5602, AP5606, AP5607, AP5616, AP92200, AP9290, AR100, AR100HD, AR202, AR203A, AR204A, AR2101, AR2102BLK, AR2144BLK, AR2145BLK, AR2200, AR2280, AR2400, AR2400FP1, AR2401, AR2407, AR2480, AR2487, AR2487G, AR2500, AR2507, AR2580, AR2587, AR2900, AR2901, AR3000, AR3100, AR3100G, AR3100SP, AR3100SP1, AR3100SP2, AR3100TAA, AR3100W, AR3100X609, AR3100X610, AR3100X617, AR3101, AR3104, AR3104SP1, AR3105, AR3105SP, AR3105W, AR3107, AR3107G, AR3107SP, AR3107X609, AR3107X610, AR3107X617, AR3130, AR3140, AR3140G, AR3140W, AR3150, AR3150SP, AR3150SP1, AR3150SP2, AR3150W, AR3150X609, AR3150X610, AR3150X617, AR3155, AR3155SP, AR3155W, AR3157, AR3157SP, AR3157X609, AR3157X610, AR3157X617, AR3200, AR3300, AR3300G, AR3300SP, AR3300W, AR3300X609, AR3300X610, AR3300X617, AR3305, AR3305SP, AR3305W, AR3307, AR3307SP, AR3307W, AR3307X609, AR3307X610, AR3307X617, AR3340, AR3340G, AR3340W, AR3347, AR3350, AR3350SP, AR3350W, AR3350X609, AR3350X610, AR3350X617, AR3355, AR3355SP, AR3355W, AR3357, AR3357SP, AR3357X609, AR3357X610, AR3357X617, AR4018, AR4018A, AR4018I, AR4018IA, AR4018IX429, AR4018IX431, AR4018IX432, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4018X431, AR4018X432, AR4024, AR4024A, AR4024I, AR4024IA, AR4024IX429, AR4024IX431, AR4024IX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4024X429, AR4024X431, AR4024X432, AR4038, AR4038A, AR4038I, AR4038IA, AR4038IX429, AR4038IX431, AR4038IX432, AR4038X429, AR4038X431, AR4038X432, AR7007, AR7050, AR7057, NBWL0356A

Technical data © 1WorldSync. Subject to technical modifications and errors.