

DIGITUS Patch cable - RJ-45 (M) to RJ-45 (M)

1 m - 3.65 mm - UTP - CAT 6a - halogen-free - molded - snagless - grey

Group	Cables & Adapters
Manufacturer	DIGITUS
Manufacturer item no.	DK-1617-A-010S
EAN/UPC	4016032461715



Description

DIGITUS slim patch cords are characterized by their small outer diameter and flexible sheath. Slim design enables versatile use in your network. Moreover, The DIGITUS Category 6A Class EA patch cords are manufactured and tested to the ISO/IEC 11801 and DIN EN 50173 Category 6 A specifications. They will guarantee the installed cabling system is compliant with the ISO & EN channel specification requirements and will provide optimum performance levels of DIGITUS Category 6A cabling. The performance is tested up to 500 MHz inclusive performance characteristics such as near end cross talk (“NEXT”). DIGITUS patch cords are designed and produced to fulfill the highest requirements of various application areas in full volume. Each cable is fitted with a molded boot which comes with kink protection and strain relief. Furthermore the boot is equipped with a latch protection that prevents the latching lever against breaking. You can easily identify the Category 6A, because of the transparent yellow colored connector.

Main features

Product Description	DIGITUS patch cable - 1 m - grey
Type	Patch cable - CAT 6a
Technology	Unshielded twisted pair (UTP)
Wires per Cable	8 wires
Features	Halogen-free, molded, snagless, Slim, flame retardant, Anti-kink sleeve, strain relief, length indication, copper conductors, bending radius 4D, transparent yellow connectors
Length	1 m
Diameter	3.65 mm
Connector	RJ-45 - male
Connector (Second End)	RJ-45 - male
Colour	Grey

Extended details

	General
Network Cable Type	Patch cable - CAT 6a
Technology	Unshielded twisted pair (UTP)
Jacket Material	Low Smoke Zero Halogen (LSZH)
American Wire Gauge (AWG)	28/7
Wires per Cable	8 wires

Pairs per Cable	4 pairs
Features	Halogen-free, molded, snagless, Slim, flame retardant, Anti-kink sleeve, strain relief, length indication, copper conductors, bending radius 4D, transparent yellow connectors
Length	1 m
Diameter	3.65 mm
Colour	Grey
	Connectivity
Connector	RJ-45 - male
Connector (Second End)	RJ-45 - male
	Miscellaneous
Compliant Standards	ISO/IEC 11801, EN 50173 - up to 500 MHz

Technical data © 1WorldSync. Subject to technical modifications and errors.