

# APC Smart-UPS SMT 2200VA LCD RM with SmartConnect

UPS (rack-mountable / external) - AC 230 V - 1980 Watt - 2200 VA - RS-232 - USB - output connectors: 9 - 2U - for P/N: AR3003 - AR3003SP - AR3006 - AR3006SP - AR3103 - AR3103SP - AR3106 - AR3106SP - AR9300SP



Group	Power Supply
Manufacturer	APC
Manufacturer item no.	SMT2200RMI2UC
EAN/UPC	0731304337324

## Description

Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

## Main features

Product Description	APC Smart-UPS SMT 2200VA LCD RM with SmartConnect - UPS - 1980 Watt - 2200 VA
Device Type	UPS - rack-mountable / external
Rack Size	2U
Weight	42.31 kg
Input Voltage	AC 230 V
Output Voltage	AC 220/230/240 V
Power Capacity	1980 Watt / 2200 VA
Input Connectors	1 x power IEC 60320 C20
Output connectors	8 x power IEC 60320 C13   1 x power IEC 60320 C19
Battery	Lead Acid
Batteries Qty	1
Run Time (Up To)	5 min at full load
Networking	RS-232, USB
Dimensions (WxDxH)	48 cm x 68.3 cm x 8.6 cm
Designed For	P/N: AR3003, AR3003SP, AR3006, AR3006SP, AR3103, AR3103SP, AR3106, AR3106SP, AR3140G, AR3340G, AR3357X674, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4024IX431, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4038IX432, AR9300SP, AR9300SP-R, AR9307SP, AR9307SP-R, NBWL0356A

## Extended details

### General

Device Type	UPS - rack-mountable / external
-------------	---------------------------------

Height (Rack Units)	2U
<b>Power Device</b>	
UPS Technology	On-line
Input Voltage	AC 230 V
Input Voltage Range	AC 160 - 286 V
Input Voltage Range (Adjustable)	AC 150 - 300 V
Frequency Provided	50/60 Hz
Frequency Required	50/60 Hz
Input Connectors	1 x power IEC 60320 C20
Power Output Connectors Details	8 x power IEC 60320 C13   1 x power IEC 60320 C19
Output Voltage	AC 220/230/240 V 50/60 Hz
Power Capacity	1980 Watt / 2200 VA
Output Waveform	Sinewave
Surge Suppression	Yes
<b>Battery</b>	
Quantity	1
Technology	Lead Acid
Features	Maintenance free, sealed, leak-proof
<b>Networking</b>	
Remote Management Interface	RS-232, USB
<b>Expansion / Connectivity</b>	
Interfaces	1 x management (RS-232) - RJ-45   1 x management (USB)
Expansion Slots	1 (total) / 1 (free) x SmartSlot
<b>Miscellaneous</b>	
Features	Audible alarm, LCD display
Compliant Standards	VDE, EN 62040-2, EAC, RCM, EN 62040-1
<b>Software / System Requirements</b>	
Software Included	APC PowerChute Business Edition
<b>Dimensions &amp; Weight</b>	
Width	48 cm
Depth	68.3 cm
Height	8.6 cm
Weight	42.31 kg
<b>Compatibility Information</b>	

Designed For

P/N: ACCS1000, ACCS1001, ACCS1002, ACCS1003, ACCS1004, ACCS1005, ACCS1006, ACCS1007, ACDC1015, ACDC1016, ACDC1017, ACDC1019, ACDC1020, ACDC1021, ACDC2513, ACF002, ACF101BLK, ACF102BLK, ACF400, AP5017, AP5602, AP5606, AP5607, AP5616, AP92200, AP9290, AR202, AR203A, AR204A, AR2101, AR2102BLK, AR2144BLK, AR2145BLK, AR2200, AR2280, AR2400, AR2400FP1, AR2401, AR2407, AR2480, AR2487, AR2487G, AR2500, AR2507, AR2580, AR2587, AR2900, AR2901, AR3000, AR3003, AR3003SP, AR3006, AR3006SP, AR3100, AR3100G, AR3100SP, AR3100SP1, AR3100SP2, AR3100TAA, AR3100W, AR3100X609, AR3100X610, AR3100X617, AR3101, AR3103, AR3103SP, AR3104, AR3104SP1, AR3105, AR3105SP, AR3105W, AR3106, AR3106SP, AR3107, AR3107G, AR3107SP, AR3107X609, AR3107X610, AR3107X617, AR3130, AR3140, AR3140G, AR3140W, AR3150, AR3150SP, AR3150SP1, AR3150SP2, AR3150W, AR3150X609, AR3150X610, AR3150X617, AR3155, AR3155SP, AR3155W, AR3157, AR3157SP, AR3157X609, AR3157X610, AR3157X617, AR3200, AR3300, AR3300G, AR3300SP, AR3300W, AR3300X609, AR3300X610, AR3300X617, AR3305, AR3305SP, AR3305W, AR3307, AR3307SP, AR3307W, AR3307X609, AR3307X610, AR3307X617, AR3340, AR3340G, AR3340W, AR3347, AR3350, AR3350SP, AR3350W, AR3350X609, AR3350X610, AR3350X617, AR3355, AR3355SP, AR3355W, AR3357, AR3357SP, AR3357X609, AR3357X610, AR3357X617, AR3357X674, AR4018, AR4018A, AR4018I, AR4018IA, AR4018IX429, AR4018IX431, AR4018IX432, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4018X431, AR4018X432, AR4024, AR4024A, AR4024I, AR4024IA, AR4024IX429, AR4024IX431, AR4024IX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4024X429, AR4024X431, AR4024X432, AR4038, AR4038A, AR4038I, AR4038IA, AR4038IX429, AR4038IX431, AR4038IX432, AR4038X432, AR7007, AR7050, AR7057, AR9300SP, AR9300SP-R, AR9307SP, AR9307SP-R, NBWL0356A

Technical data © 1WorldSync. Subject to technical modifications and errors.