

HONEYWELL Datamax MP-Series Compact4 Mark III

Label printer - direct thermal - Roll (11.5 cm) - 200 dpi - up to 125 mm/sec - USB - LAN - serial - peeler

Group	Printers
Manufacturer	HONEYWELL
Manufacturer item no.	XG9-00-03000000



Description

The MP Compact4 Mark III printers provide label-printing solutions, that offer great customer benefits despite their small size. The MP printers are manufactured to the high standards and feature a die-cast frame and metal cover for protection, making them durable and reliable in demanding industrial environments.

Main features

Product Description	Datamax MP-Series Compact4 Mark III - label printer - B/W - direct thermal
Printer Type	Label printer - direct thermal - B/W
Weight	3.5 kg
Localisation	Europe
Max Media Size	Roll (11.5 cm)
Min Media Size (Custom)	40 mm x 10 mm
Max Media Size (Custom)	115 mm
Print Speed	Up to 125 mm/sec - max speed
Max Resolution (B&W)	200 dpi
Interface	USB, LAN, serial
RAM Installed (Max)	64 MB
Flash Memory Installed (Max)	128 MB
Language Simulation	ZPL, DPL
Media Type	Continuous paper labels, die cut labels, fanfold labels
Features	Label Taken Sensor (LTS), peeler
Networking	Print server
Power	AC 120/230 V
Dimensions (WxDxH)	23 cm x 26 cm x 10.5 cm

Extended details

	General
Printer Type	Label printer - direct thermal - monochrome
Localisation	Europe

Printer	
Print Speed	Up to 125 mm/sec - max speed - 200 dpi
Built-in Devices	Tear bar
Connectivity Technology	Wired
Interface	USB, LAN, serial
Max Resolution (B&W)	200 dpi
Language Simulation	ZPL, DPL
Features	Label Taken Sensor (LTS), peeler
RAM	
RAM Installed (Max)	64 MB
Flash Memory	
Flash Memory	128 MB
Media Handling	
Media Type	Continuous paper labels, die cut labels, fanfold labels
Max Media Size	Roll (11.5 cm)
Min Media Size (Custom)	40 mm x 10 mm
Max Media Size (Custom)	115 mm
Media Sizes	Roll (4 - 11.5 cm)
Max Printing Width	115 mm
Media Thickness Range	0.058 mm - 0.18 mm
Roll Maximum Outer Diameter	100 mm
Roll Core Diameter	40 mm
Media Feeders	1 x manual - 1 roll - Roll (11.5 cm)
Networking	
Networking	Print server
Expansion / Connectivity	
Connections	1 x LAN - RJ-45 1 x RS-232 - 9 pin D-Sub (DB-9) 1 x USB
Miscellaneous	
Cables Included	1 x USB cable 1 x serial cable 1 x network cable
Power	
Power Device	Power supply
Voltage Required	AC 120/230 V
Frequency Required	50/60 Hz
Environmental Parameters	
Min Operating Temperature	5 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 95% (non-condensing)
Dimensions & Weight	
Width	23 cm

Depth	26 cm
Height	10.5 cm
Weight	3.5 kg

Technical data © 1WorldSync. Subject to technical modifications and errors.