

HONEYWELL RP2 - Label printer

direct thermal - Roll (11 cm) - 203 dpi - up to 127 mm/sec - USB 2.0 - NFC - Bluetooth 4.0

Group	Printers
Manufacturer	HONEYWELL
Manufacturer item no.	RP2A0000B00
EAN/UPC	4053199515271



Description

If you're looking for an ultra-rugged and reliable mobile receipt printer for route accounting, direct store delivery, citation printing, car rental return receipts and more, look no further than the RP Series. This tough competitor withstands drops and exposure to dust and water, and is designed for all-day printing with a full-shift battery life.

Main features

Product Description	Honeywell RP2 - label printer - B/W - direct thermal
Printer Type	Label printer - direct thermal - B/W
Form Factor	Portable
Weight	720 g
Max Media Size	Roll (11 cm)
Min Media Size (Custom)	25 mm
Max Media Size (Custom)	57 mm
Print Speed	Up to 127 mm/sec - max speed
Max Resolution (B&W)	203 dpi
Interface	USB 2.0, NFC, Bluetooth 4.0
Language Simulation	ZPL II, Intermec Printer Language (IPL), Extensible Mark-up Language (XML), Comtec Printer Control Language (CPCL), DPL
Media Type	Labels, receipt paper
Battery	Required 1 Lithium Ion Included Qty 1
Dimensions (WxDxH)	11.6 cm x 7.7 cm x 16 cm

Extended details

	General
Printer Type	Label printer - direct thermal - monochrome
	Printer
Print Speed	Up to 127 mm/sec - max speed
Connectivity Technology	Wireless
Interface	USB 2.0, NFC, Bluetooth 4.0
Max Resolution (B&W)	203 dpi

Language Simulation	ZPL II, Intermec Printer Language (IPL), Extensible Mark-up Language (XML), Comtec Printer Control Language (CPCL), DPL
---------------------	---

Media Handling

Media Type	Labels, receipt paper
Max Media Size	Roll (11 cm)
Min Media Size (Custom)	25 mm
Max Media Size (Custom)	57 mm
Media Sizes	Roll (2.5 - 5.7 cm)
Max Printing Width	48 mm
Media Thickness Range	0.05 mm - 0.16 mm
Roll Maximum Outer Diameter	58 mm
Roll Core Diameter	25.4 mm, 19 mm, 10.16 mm
Media Feeders	1 x manual - 1 roll - Roll (11 cm)

Expansion / Connectivity

Connections	1 x USB 2.0
-------------	-------------

Miscellaneous

Compliant Standards	IP54
---------------------	------

Battery

Type	Lithium Ion
Required Qty	1
Included	1
Capacity	2500 mAh

Environmental Parameters

Min Operating Temperature	-20 °C
Max Operating Temperature	55 °C
Humidity Range Operating	10 - 90% (non-condensing)

Dimensions & Weight

Width	11.6 cm
Depth	7.7 cm
Height	16 cm
Weight	720 g

Technical data © 1WorldSync. Subject to technical modifications and errors.