

# Lexmark MX722dhe - Multifunction printer

B/W - laser - 215.9 x 355.6 mm (original) - A4/Legal (media) - up to 66 ppm (copying) - up to 66 ppm (printing) - 650 sheets - USB 2.0 - Gigabit LAN - USB 2.0 host



Group	Multifunction Printers
Manufacturer	Lexmark
Manufacturer item no.	25B0333
EAN/UPC	0734646720427

## Description

The multifunction product with features and performance to satisfy even large workgroups.

## Main features

Product Description	Lexmark MX722dhe - multifunction printer - B/W
Device Type	Multifunction printer
Printing Technology	Laser (monochrome)
Monthly Duty Cycle (max)	350000 pages
Recommended Monthly Volume	5000 - 100000 pages
Max Copying Speed	Up to 66 ppm
Max Printing Speed	Up to 66 ppm
Max Printing Resolution	Up to 1200 x 1200 dpi
Max Printing Resolution Class	Up to 1200 x 1200 dpi
Scanning	600 x 600 dpi
Display	7"
Original Size	215.9 x 355.6 mm (max)
Original Type	Sheets
Document Feeder Capacity	200 sheets
Media Size	Legal (216 x 356 mm), A4 (210 x 297 mm) (max)

Media Type	Transparencies, envelopes, plain paper, labels, card stock
Standard Media Capacity	650 sheets
Max Media Capacity	3300 sheets
Bypass Feeder Capacity	100 sheets
Output Trays Capacity	550 sheets
Automatic Duplexing	Yes (copying) Yes (printing) Yes (scanning)
Connection Availability	Yes
Interface	USB 2.0, Gigabit LAN, USB 2.0 host
AirPrint Enabled	Yes
Office Machine Features	Scan to e-mail, scan to FTP, scan to PC, scan to USB host, internal card slot
Dimensions (WxDxH)	55.88 cm x 57.84 cm x 73.91 cm
Weight	44.1 kg
Environmental Standards	EPEAT Gold, ENERGY STAR Qualified

## Extended details

General	
Printer Fonts	Bitmapped PCL x 2   Scalable PostScript x 158   Scalable PCL x 84   Scalable PPDS x 39
Device Type	Multifunction printer
Printing Technology	Laser - monochrome
Monthly Duty Cycle (max)	350000 pages
Recommended Monthly Volume	5000 - 100000 pages
Display Diagonal Size	7"
Display Colour Support	Colour
Display Features	Touch screen
Connection Availability	Yes
Interface	USB 2.0, Gigabit LAN, USB 2.0 host

AirPrint Enabled	Yes
Office Machine Features	Scan to e-mail, scan to FTP, scan to PC, scan to USB host, internal card slot
	<b>Memory</b>
Standard Memory	2 GB
Max Supported Memory	6 GB
	<b>Copying</b>
Max Copying Speed	Up to 66 ppm
Max Document Enlargement	400%
Max Document Reduction	25%
Automatic Duplexing	Yes
	<b>Printing</b>
Max Printing Resolution	Up to 1200 x 1200 dpi
Max Printing Resolution Class	Up to 1200 x 1200 dpi
Max Printing Speed	Up to 66 ppm
Printer Drivers / Emulations	PCL 5e, PCL 6, PostScript 3, PPDS, PDF 1.7, XPS
Image Enhancement Technology	1200 IQ, 2400 IQ
Automatic Duplexing	Yes
First Print Out Time B/W	4 sec
Colour Management Features	Mopria
	<b>Scanning</b>
Scan Element	CCD
Automatic Duplexing	Yes
Optical Resolution	600 x 600 dpi

### Document & Media Handling

Max Original Size	215.9 x 355.6 mm
Original Type	Sheets
Document Feeder Capacity	200 sheets
Max Media Size	A4/Legal
Supported Media Type	Transparencies, envelopes, plain paper, labels, card stock
Supported Media Sizes	ANSI A (Letter) (216 x 279 mm), Legal (216 x 356 mm), Executive (184 x 267 mm), A4 (210 x 297 mm), A5 (148 x 210 mm), A6 (105 x 148 mm), Folio (216 x 330 mm), JIS B5 (182 x 257 mm), Statement (139.7 x 215.9 mm), Oficio (216 x 343 mm)
Supported Envelope Sizes	US No 10 (104.7 x 241.3 mm), International DL (110 x 220 mm), International C5 (162 x 229 mm), International B5 (176 x 250 mm), Monarch (98.4 x 190.5 mm), US No 9 (98.6 x 225.6 mm)
Standard Media Capacity	650 sheets
Max Media Capacity	3300 sheets
Bypass Feeder Capacity	100 sheets
Output Trays Capacity	550 sheets
Document & Media Handling Details	Input tray - 550 sheets weight: 60 g/m <sup>2</sup> - 176 g/m <sup>2</sup> ; weight (lbs): 16 lbs - 47 lbs   Bypass tray - 100 sheets   Output tray - 550 sheets   RADF - 200 sheets
Speed Details	Printing: up to 66 ppm (A4) - B/W (ISO/IEC 24734)   Printing: up to 40 spm (A4) - B/W duplex (ISO/IEC 24734)   Printing: up to 70 ppm (Letter A) - B/W (ISO/IEC 24734)   Printing: up to 42 spm (Letter A) - B/W duplex (ISO/IEC 24734)   Copying: up to 66 ppm (A4) - B/W (ISO/IEC 24735)   Copying: up to 42 spm (A4) - B/W duplex (ISO/IEC 24735)   Scanning: up to 72 spm (A4) - colour   Scanning: up to 75 spm (Letter A) - colour   Scanning: up to 72 spm (A4) - B/W   Scanning: up to 75 spm (Letter A) - B/W   Scanning: up to 144 spm (A4) - colour   Scanning: up to 150 spm (Letter A) - colour   Scanning: up to 144 spm (A4) - B/W   Scanning: up to 150 spm (Letter A) - B/W   Copying: up to 70 ppm (Letter A) - B/W (ISO/IEC 24735)   Copying: up to 44 spm (Letter A) - B/W duplex (ISO/IEC 24735)
<b>Connections</b>	
Interfaces	1 x USB 2.0 - 4 pin USB Type B   1 x Gigabit LAN - RJ-45   2 x USB 2.0 host - 4 pin USB Type A
Security Protocols & Features	SSL, LEAP, TLS, IPsec, 802.1x, ARP, TTLS, PEAP, MD5, MS-CHAPv2, IPv6 support
Operating System Support	SuSE Linux Enterprise Server 10, SuSE Linux Enterprise Server 11, Sun Solaris 10, Novell NetWare 6.5, IBM AIX 6.1, Apple Mac OS X 10.6, Apple Mac OS X 10.7, Red Hat Enterprise Linux WS 6.0, IBM AIX 7.1, Apple Mac OS X 10.8, Novell Open Enterprise Server, Apple Mac OS X 10.9, MS Windows 7 (32/64 bits), Debian Linux 7.0, Sun Solaris 11, Apple Mac OS X 10.10, Windows 8 (32/64-bits), Windows 8.1 (32/64-bits), Windows 10, Apple Mac OS X 10.11, openSUSE 13.2, Novell Open Enterprise Server 2, Debian Linux 8.0, SuSE Linux Enterprise Server 12, Novell Open Enterprise Server 11, Red Hat Enterprise Linux WS 7.0, macOS 10.12, Fedora 24, openSUSE 42.3, Ubuntu Linux 16.04 LTS, Fedora 23, Apple Mac OS X 10.13, Novell NetWare 5.1 SP6 or later, Novell NetWare 6.0 SP3 or later

	<b>Power</b>
Power Consumption Operational	890 Watt
Power Consumption Standby	42 Watt
Power Consumption Sleep	0.2 Watt
	<b>Miscellaneous</b>
First Copy Out Time B/W	4 sec
Consumables Included	1 x toner cartridge (black) - up to 11000 pages   1 x imaging unit - up to 150000 pages
Compliant Standards	FCC Class A certified, C-Tick, CISPR 22 Class A, NOM, CCC, DOC, ICES-003 Class A, SII, UL 60950-1, KCC, A-Tick, IEC 60825-1, FDA, UL-AR, GOST-R, EN 60825-1, BSMI Class A, CDRH, KC, CECP, CEL, VCCI Class A, Bel GISS, ECMA-370, EFTA, TER, MET, ISO 532B, TED, CCD 035 EcoLogo, IEC/EN 60950-1, CAN/CSA-C22.2 No. 60950-1, RAL-UZ 205, UL-GS
	<b>Environmental Standards</b>
EPEAT Compliant	EPEAT Gold
ENERGY STAR Certified	Yes
	<b>Manufacturer Warranty</b>
Service & Support	Limited warranty - 1 year - on-site - response time: next business day
	<b>Dimensions &amp; Weight</b>
Width	55.88 cm
Depth	57.84 cm
Height	73.91 cm
Weight	44.1 kg
	<b>Dimensions &amp; Weight (Shipping)</b>
Shipping Width	70 cm
Shipping Depth	73.5 cm
Shipping Height	102 cm
Shipping Weight	58.6 kg
	<b>Environmental Parameters</b>
Sound Emission	14 dBA (idle) / 60 dBA (operating)
Min Operating Temperature	10 °C

Max Operating Temperature	32 °C
---------------------------------	-------

Humidity Range Operating	8 - 80%
--------------------------------	---------

Technical data © 1WorldSync. Subject to technical modifications and errors.