

APC Smart-UPS - UPS - AC 230 V

4 kW - 5000 VA - Ethernet 10/100 - RS-232 - output connectors: 10 - 5U - black - for P/N: AR3105W - AR3140G - AR3155W - AR3305W - AR3340G - AR3355W - AR4038IX432 - NBWL0356A

Group	Power Supply
Manufacturer	APC
Manufacturer item no.	SUA5000RMI5U
EAN/UPC	0731304255321



Description

APC Smart-UPS protects your data by supplying reliable, network-grade power in either traditional Tower or Rack-optimized form factors for space constrained business critical applications. Award winning APC Smart-UPS is the perfect UPS for protecting business critical file servers (Intel or UNIX based), minicomputers, network switches and hubs, Point of Sale, retail/bank back office and ATMs. Rack Mount versions are the choice for rack optimized servers, server appliances, blade servers, other blade devices and rack-mounted network switches and hubs.

Main features

Product Description	APC Smart-UPS - UPS - 4 kW - 5000 VA
Device Type	UPS - external
Rack Size	5U
Weight	97.7 kg
Input Voltage	AC 230 V
Output Voltage	AC 220/230/240 V ± 5%
Power Capacity	4 kW / 5000 VA
Input Connectors	1 x hardwire 3-wire
Output connectors	8 x power IEC 60320 C13 2 x power IEC 60320 C19
Battery	Lead Acid
Battery Form Factor	Internal
Batteries Qty	2
Run Time (Up To)	9.4 min at full load
Networking	Ethernet 10/100, RS-232
Remote Management Protocol	SNMP, Telnet, HTTP
Colour	Black
Dimensions (WxDxH)	48.3 cm x 66 cm x 22.2 cm
Designed For	P/N: AR2200, AR2280, AR2487G, AR3100TAA, AR3100W, AR3105SP, AR3105W, AR3107G, AR3107SP, AR3140G, AR3140W, AR3150SP, AR3150W, AR3155SP, AR3155W, AR3157SP, AR3300SP, AR3300W, AR3305SP, AR3305W, AR3307SP, AR3307W, AR3340G, AR3340W, AR3350SP, AR3350W, AR3355SP, AR3355W, AR3357SP, AR4038IX432, NBWL0356A

Extended details

General	
Device Type	UPS - external
Battery Enclosure Type	Internal
Height (Rack Units)	5U
Colour	Black
Power Device	
UPS Technology	Line interactive
Input Voltage	AC 230 V
Input Voltage Range	AC 160 - 286 V
Input Voltage Range (Adjustable)	AC 151 - 302 V
Frequency Provided	50/60 Hz
Frequency Required	50/60 Hz
Input Connectors	1 x hardwire 3-wire
Power Output Connectors Details	8 x power IEC 60320 C13 2 x power IEC 60320 C19
Output Voltage	AC 220/230/240 V ± 5% - 50/60 Hz
Power Capacity	4 kW / 5000 VA
Output Waveform	Sinewave
Surge Suppression	Yes
Surge Energy Rating	480 Joules
Battery	
Quantity	2
Technology	Lead Acid
Run Time (Up To)	9.4 min at full load
Recharge Time	3 hours
Networking	
Remote Management Interface	Ethernet 10/100, RS-232
Remote Management Protocol	SNMP, Telnet, HTTP
Expansion / Connectivity	
Interfaces	1 x management (RS-232) - 9 pin D-Sub (DB-9) 1 x management (Ethernet) - RJ-45
Expansion Slots	1 (total) / 0 (free) x SmartSlot
Miscellaneous	
Cables Included	Serial cable - external
Rack Mounting Kit	Included
Features	Audible alarm, LED indicators, noise filtering
Compliant Standards	C-Tick, GOST, GS, VDE, EN 50091-2, EN 50091-1
Software / System Requirements	
Software Included	APC PowerChute Business Edition
Manufacturer Warranty	

Service & Support	Limited warranty - 2 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95%
Sound Emission	53 dBA
Dimensions & Weight	
Width	48.3 cm
Depth	66 cm
Height	22.2 cm
Weight	97.7 kg
Dimensions & Weight (Shipping)	
Shipping Width	61 cm
Shipping Depth	76.2 cm
Shipping Height	63.5 cm
Shipping Weight	107 kg
Compatibility Information	
Designed For	P/N: ACCS1000, ACCS1001, ACCS1002, ACCS1003, ACCS1004, ACCS1005, ACCS1006, ACCS1007, ACDC1015, ACDC1016, ACDC1017, ACDC1019, ACDC1020, ACDC1021, ACDC2513, ACF001, ACF002, ACF003, ACF101BLK, ACF102BLK, ACF201BLK, ACF400, AP5017, AP5602, AP5606, AP5607, AP5616, AP92200, AP9290, AR202, AR2101, AR2102BLK, AR2200, AR2280, AR2400, AR2400FP1, AR2401, AR2407, AR2480, AR2487, AR2487G, AR2500, AR2507, AR2580, AR2587, AR2900, AR2901, AR3000, AR3100, AR3100G, AR3100SP, AR3100TAA, AR3100W, AR3100X609, AR3100X610, AR3100X617, AR3101, AR3104SP1, AR3105, AR3105SP, AR3105W, AR3107G, AR3107SP, AR3107X609, AR3107X610, AR3107X617, AR3130, AR3140G, AR3140W, AR3150, AR3150SP, AR3150W, AR3150X609, AR3150X610, AR3150X617, AR3155, AR3155SP, AR3155W, AR3157SP, AR3157X609, AR3157X610, AR3157X617, AR3200, AR3300, AR3300G, AR3300SP, AR3300W, AR3300X609, AR3300X610, AR3300X617, AR3305, AR3305SP, AR3305W, AR3307, AR3307SP, AR3307W, AR3307X609, AR3307X610, AR3307X617, AR3340, AR3340G, AR3340W, AR3347, AR3350, AR3350SP, AR3350W, AR3350X609, AR3350X610, AR3350X617, AR3355, AR3355SP, AR3355W, AR3357, AR3357SP, AR3357X609, AR3357X610, AR3357X617, AR3810, AR3812, AR3814, AR4038, AR4038A, AR4038I, AR4038IA, AR4038IX429, AR4038IX431, AR4038IX432, AR4038X429, AR4038X431, AR4038X432, AR7007, AR7050, AR7057, AR8135BLK, NBWL0356A

Technical data © 1WorldSync. Subject to technical modifications and errors.