

APC Replacement Battery Cartridge #24

UPS battery - Lead Acid - black - for P/N: DLA1500RM2U -SU1400R2IBX135 - SUA1500R2ICH - SUA1500RM2U-BR -SUA1500RM2UTW

| Group | UPS Accessories |
|-----------------------|-----------------|
| Manufacturer | APC |
| Manufacturer item no. | RBC24 |
| EAN/UPC | 0731304015772 |



Description

In the E-world where businesses can't stop and downtime is measured in dollars, American Power Conversion (APC) provides protection against some of the leading causes of downtime, data loss and hardware damage: power problems and temperature. As a global leader in power availability solutions, APC sets the standard in its industry for quality, innovation and support. Its comprehensive power solutions, which are designed for both home and corporate environments, improve the manageability, availability and performance of sensitive electronic, network, communications and industrial equipment of all sizes.

Main features

| Product Description | APC Replacement Battery Cartridge #24 - UPS battery - Lead Acid |
|---------------------|---|
| Device Type | UPS battery |
| Weight | 11.9 kg |
| Battery | Lead Acid |
| Battery Form Factor | Plug-in module |
| Colour | Black |
| Dimensions (WxDxH) | 21.6 cm x 34.3 cm x 8.3 cm |
| Designed For | P/N: DLA1500RM2U, DLA1500RMI2U, SU1400R2BX120, SU1400R2IBX120, SU1400R2IBX135, SU1400R2X122, SU1400RM2U, SU1400RM2UX93, SU1400RMI2U, SU1400RMX176, SUA1500R2ICH, SUA1500R2X122, SUA1500R2X138, SUA1500R2X180, SUA1500R2X93, SUA1500RM2U, SUA1500RM2U-BR, SUA1500RM2UTW, SUA1500RMI2U, SUA1500RMUS |

Extended details

| | General |
|------------------------|----------------------------|
| Device Type | UPS battery |
| Battery Enclosure Type | Plug-in module |
| Colour | Black |
| | Battery |
| Technology | Lead Acid |
| Features | Spill-proof |
| | Manufacturer Warranty |
| Service & Support | Limited warranty - 2 years |
| | |



| | Environmental Parameters |
|---------------------------|---|
| Min Operating Temperature | 0 °C |
| Max Operating Temperature | 40 °C |
| Min Storage Temperature | -15 °C |
| Max Storage Temperature | 45 °C |
| Humidity Range Operating | 0 - 95% |
| | Dimensions & Weight |
| Width | 21.6 cm |
| Depth | 34.3 cm |
| Height | 8.3 cm |
| Weight | 11.9 kg |
| | Dimensions & Weight (Shipping) |
| Shipping Width | 36.8 cm |
| Shipping Depth | 49.5 cm |
| Shipping Height | 15.2 cm |
| Shipping Weight | 12.6 kg |
| | Compatibility Information |
| Designed For | P/N: DLA1500RM2U, DLA1500RMI2U, SU1400R2BX120, SU1400R2IBX120, SU1400R2IBX135, SU1400R2X122, SU1400RM2U, SU1400RM2UX93, SU1400RMI2U, SU1400RMX176, SUA1500R2ICH, SUA1500R2X122, SUA1500R2X138, SUA1500R2X180, SUA1500R2X93, SUA1500RM2U, SUA1500RM2U-BR, SUA1500RM2UTW, SUA1500RMI2U, SUA1500RMUS |
| | |

Technical data $\textcircled{\mbox{\scriptsize only}}$ 1WorldSync. Subject to technical modifications and errors.