

Epson EB-L200SX - 3LCD projector

3600 lumens (white) - 3600 lumens (colour) - XGA (1024 x 768) - 4:3
 - 802.11a/b/g/n/ac wireless / LAN/ Miracast - white

| | |
|-----------------------|---------------|
| Group | Projectors |
| Manufacturer | Epson |
| Manufacturer item no. | V11H994040 |
| EAN/UPC | 8715946686417 |



Description

Whatever the size of workspace, unrestricted and immersive presentations are now possible with this compact, affordable display solution. Due to a large display size, and flexible formats, content can be viewed from every angle, and participants can share directly from their own devices, for the perfect collaborative experience.

Main features

| | |
|-------------------------------|--|
| Product Description | Epson EB-L200SX - 3LCD projector - 802.11a/b/g/n/ac wireless / LAN/ Miracast - white |
| Device Type | 3LCD projector |
| Colour | White |
| Built-in Devices | Speaker |
| Brightness (White) | 3600 lumens |
| Brightness (Colour) | 3600 lumens |
| Contrast Ratio | 2500000:1 (dynamic) |
| Resolution | XGA (1024 x 768) |
| Native Aspect Ratio | 4:3 |
| Colour Support | 1.07 billion colours |
| Bulb type | Laser |
| Bulb life cycle | Up to 20000 hour(s) - normal mode Up to 30000 hour(s) - economic mode |
| Video Input | IEEE 802.11a/b/g/n/ac wireless / LAN/ Miracast |
| Speakers | Speaker(s) - integrated |
| Environmental Standards | TCO Certified Projectors 8 |
| Power | AC 220 - 240 V (50 - 60 Hz) |
| Power Consumption Operational | 254 Watt |

Dimensions (WxDxH) 32.5 cm x 33.7 cm x 9 cm

Weight 4.5 kg

Extended details

General

Device Type 3LCD projector

Built-in Devices Speaker

Networking 802.11a/b/g/n/ac, Ethernet

Enclosure Colour White

Projector

Brightness (White) 3600 lumens

Brightness (Colour) 3600 lumens

Brightness (Reduced) 2520 lumens

Contrast Ratio 2500000:1 (dynamic)

Image Size 127 cm - 284.5 cm

Throw Ratio 0.55 - 0.74:1

Digital Zoom Factor 1.35x

Resolution XGA - XGA (1024 x 768)

Native Aspect Ratio 4:3

Colour Support 1.07 billion colours

Bulb type Laser

Bulb life cycle Up to 20000 hour(s) - normal mode | Up to 30000 hour(s) - economic mode

Features EPSON 3LCD technology, Dynamic Mode, Cinema Mode

Lens

Focus Type Manual

Lens Aperture F/1.6

Keystone Correction Direction Horizontal, vertical

Vertical Keystone Correction -15 / +15

Horizontal Keystone Correction -15 / +15

Video Input

Video Interfaces VGA, HDMI

LAN and Wireless Image Transferring Protocols Wired LAN, Miracast, IEEE 802.11ac

Speakers

Type Integrated

Sound Output Mode Mono

Output Power / Channel 16 Watt

Speakers 1 x mixed channel

Expansion / Connectivity

Interfaces 1 x USB 2.0 - 4 pin USB Type A | 1 x USB 2.0 - 4 pin USB Type B | 2 x VGA input | 1 x VGA output | 2 x HDMI input | 1 x network - RJ-45 | 1 x audio line-out - mini-phone stereo 3.5 mm | 2 x audio line-in - mini-phone stereo 3.5 mm | 1 x microphone input - mini-phone 3.5 mm | 1 x serial RS-232C

Miscellaneous

Included Accessories Remote control, battery for remote control

Cables Included 1 x HDMI cable

Security Features Security lock slot (cable lock sold separately), password protection, control panel lock, Wireless LAN Lock, padlock, security cable hole

Security Slot Type Kensington security slot

Environmental Standards

TCO Certified TCO Certified Projectors 8

Power

Power Source AC

Voltage Required AC 220 - 240 V (50 - 60 Hz)

Power Consumption Operational 254 Watt

Power Consumption Stand by 0.5 Watt

Dimensions & Weight

Width 32.5 cm

Depth 33.7 cm

Height 9 cm

Weight 4.5 kg

Manufacturer Warranty

Service & Support Limited warranty - 5 years / 12000 hours - carry-in

Environmental Parameters

| | |
|-----------------------------------|--------|
| Sound Emission | 36 dBA |
| Sound Emission (Economic Mode) | 26 dBA |

Technical data © 1WorldSync. Subject to technical modifications and errors.