

Lexmark MarkNet N8352 - Print server

802.11b/g/n - for Lexmark MX310dn - MX317dn - MX410de - MX417de - XM1145

Group	Printing Accessories
Manufacturer	Lexmark
Manufacturer item no.	27X0129
EAN/UPC	0734646409452



Description

Place assets where they are needed - printer location is functionally and economically driven, not constrained by existing LAN connections. SNMPv3 supports encrypted and authenticated management traffic protecting remote configuration and device status messages. IPSec can be used with both TCP/IP IPv4 and IPv6 networks and provides encryption and authentication of communications at the network layer.

Main features

Product Description	Lexmark MarkNet N8352 - print server
Device Type	Print server
Data Link Protocol	802.11b/g/n
Data Transfer Rate	72 Mbps
Network / Transport Protocol	TCP/IP, AppleTalk, UDP/IP, NTP, ICMP/IP, IPSec, LPR/LPD, ARP, FTP, BOOTP, DHCP, DNS, RARP, Bonjour, SLP, DDNS
Compliant Standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.1x, IEEE 802.11i, IEEE 802.11n
System Requirements	Apple MacOS X, HP-UX 11.11, Novell NetWare 6.5, Novell NetWare 5.1 SP6 or later, Novell NetWare 6.0 SP3 or later, HP-UX 11.23, IBM AIX 5.3, SunSoft Solaris x86 10, Red Hat Enterprise Linux WS 4, Novell Open Enterprise Server, SuSE Linux Enterprise Server 11, Microsoft Windows Server 2008 R2, SUSE Linux Enterprise Desktop 11, Debian GNU/Linux 5.0, SUSE Linux Enterprise Desktop 10, SuSE Linux Enterprise Server 10, Red Hat Enterprise Linux WS 5, IBM AIX 6.1, Microsoft Windows Vista (32/64 bits), HP-UX 11.31, Linspire 6.0, Red Flag Linux Desktop 6.0, openSUSE 11.3, Linux Linpus Desktop 9.6, Microsoft Windows 7 (32/64 bits), Microsoft Windows XP (32/64 bits), Microsoft Windows Server 2008 (32/64-bits), Microsoft Windows Server 2003 (32/64-bits), SunSoft Solaris SPARC Platform Edition 9, SunSoft Solaris SPARC Platform Edition 10, Red Hat Fedora 14, Red Hat Fedora 15, openSUSE 11.4, IBM AIX 7.1, Ubuntu 11.04, Linux Mint 11, SunSoft Solaris x86 11, Ubuntu 11.10, Debian GNU/Linux 6.0, Linux Mint 9, Linux Mint 10, Red Hat Enterprise Linux WS 6, Ubuntu 12.04, openSUSE 12.1, PCLinuxOS 2011.9, Linux Mint 12
Designed For	Lexmark MX310dn, MX317dn, MX410de, MX417de, XM1145

Extended details

	General
Device Type	Print server
	Networking
Connectivity Technology	Wireless

Data Link Protocol	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Data Transfer Rate	72 Mbps
Network / Transport Protocol	TCP/IP, AppleTalk, UDP/IP, NTP, ICMP/IP, IPSec, LPR/LPD, ARP, FTP, BOOTP, DHCP, DNS, RARP, Bonjour, SLP, DDNS
Remote Management Protocol	Telnet, SNMP 3, HTTP, HTTPS, TFTP, IPP 1.0, IPP 1.1, IPP 2.0
Compliant Standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.1x, IEEE 802.11i, IEEE 802.11n
	Miscellaneous
Encryption Algorithm	128-bit WEP, 64-bit WEP, SSL, TLS, WPA2
	Software / System Requirements
OS Required	Apple MacOS X, HP-UX 11.11, Novell NetWare 6.5, Novell NetWare 5.1 SP6 or later, Novell NetWare 6.0 SP3 or later, HP-UX 11.23, IBM AIX 5.3, SunSoft Solaris x86 10, Red Hat Enterprise Linux WS 4, Novell Open Enterprise Server, SuSE Linux Enterprise Server 11, Microsoft Windows Server 2008 R2, SUSE Linux Enterprise Desktop 11, Debian GNU/Linux 5.0, SUSE Linux Enterprise Desktop 10, SuSE Linux Enterprise Server 10, Red Hat Enterprise Linux WS 5, IBM AIX 6.1, Microsoft Windows Vista (32/64 bits), HP-UX 11.31, Linspire 6.0, Red Flag Linux Desktop 6.0, openSUSE 11.3, Linux Linpus Desktop 9.6, Microsoft Windows 7 (32/64 bits), Microsoft Windows XP (32/64 bits), Microsoft Windows Server 2008 (32/64-bits), Microsoft Windows Server 2003 (32/64-bits), SunSoft Solaris SPARC Platform Edition 9, SunSoft Solaris SPARC Platform Edition 10, Red Hat Fedora 14, Red Hat Fedora 15, openSUSE 11.4, IBM AIX 7.1, Ubuntu 11.04, Linux Mint 11, SunSoft Solaris x86 11, Ubuntu 11.10, Debian GNU/Linux 6.0, Linux Mint 9, Linux Mint 10, Red Hat Enterprise Linux WS 6, Ubuntu 12.04, openSUSE 12.1, PCLinuxOS 2011.9, Linux Mint 12
	Compatibility Information
Designed For	Lexmark MX310dn, MX317dn, MX410de, MX417de, XM1145

Technical data © 1WorldSync. Subject to technical modifications and errors.