

APC Smart-UPS X 1000 Rack/Tower LCD

UPS (rack-mountable) - AC 230 V - 800 Watt - 1000 VA - RS-232 - USB - output connectors: 8 - 2U - black

Group	Power Supply
Manufacturer	APC
Manufacturer item no.	SMX1000I
EAN/UPC	0731304268635



Description

Provides clear and accurate information in multiple languages with the ability to configure the UPS locally with easy to use navigation keys. Patent-pending operating mode that bypasses unused electrical components in good power conditions to achieve very high operating efficiency without sacrificing any protection.

Main features

Product Description	APC Smart-UPS X 1000 Rack/Tower LCD - UPS - 800 Watt - 1000 VA
Device Type	UPS - rack-mountable
Rack Size	2U
Weight	22.9 kg
Input Voltage	AC 230 V
Output Voltage	AC 230 V
Power Capacity	800 Watt / 1000 VA
Input Connectors	1 x power IEC 60320 C14
Output connectors	8 x power IEC 60320 C13
Battery	Lead Acid
Run Time (Up To)	8.1 min at full load
Networking	RS-232, USB
Colour	Black
Dimensions (WxDxH)	43.2 cm x 49 cm x 8.9 cm

Extended details

General	
Device Type	UPS - rack-mountable
Height (Rack Units)	2U
Colour	Black
Power Device	
UPS Technology	Line interactive
Input Voltage	AC 230 V

Input Voltage Range	AC 160 - 285 V
Input Voltage Range (Adjustable)	AC 151 - 302 V
Frequency Provided	47 - 63 Hz
Input Connectors	1 x power IEC 60320 C14
Power Output Connectors Details	8 x power IEC 60320 C13
Output Voltage	AC 230 V 47 - 63 Hz
Power Capacity	800 Watt / 1000 VA
Output Waveform	Sinewave
Surge Suppression	Yes
Surge Energy Rating	600 Joules
Circuit Protection	Circuit breaker
Battery	
Technology	Lead Acid
Run Time (Up To)	8.1 min at full load 24.2 min at half load
Recharge Time	3 hours
Networking	
Remote Management Interface	RS-232, USB
Expansion / Connectivity	
Interfaces	1 x EPO (emergency power off) 1 x management (RS-232) 1 x USB
Expansion Slots	1 (total) / 1 (free) x SmartSlot
Miscellaneous	
Cables Included	Serial cable - external USB cable - external Power cable 1.8 m
Rack Mounting Kit	Included
Features	Audible alarm, emergency power off, LCD display, noise filtering
Compliant Standards	C-Tick, UL 1449, VDE, EN 50091-2, RoHS Exemption 7b, RoHS, EN 50091-1, REACH
Software / System Requirements	
Software Included	APC PowerChute Business Edition
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years Limited warranty - batteries - 2 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95%
Sound Emission	40 dBA
Dimensions & Weight	
Width	43.2 cm
Depth	49 cm
Height	8.9 cm

Weight	22.9 kg
--------	---------

Dimensions & Weight (Shipping)	
---	--

Shipping Width	58.9 cm
----------------	---------

Shipping Depth	62 cm
----------------	-------

Shipping Height	24.6 cm
-----------------	---------

Shipping Weight	27.3 kg
-----------------	---------

Technical data © 1WorldSync. Subject to technical modifications and errors.